# INTERNATIONAL **STANDARD**

ISO/IEC 13818-4

> Second edition 2004-12-15 **AMENDMENT 2** 2005-06-15

Information technology —Generic coding of moving pictures and associated audio information —

Part 4:

Conformance testing

AMENDMENT 2: Additional audio conformance test sequences

Technologies de l'information — Codage générique des images animées et des informations sonores associées —

Partie 4: Essais de conformité

ECNORM. Chick to vie AMENDEMENT 2: Séquences d'essais de conformité sonores additionnels



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2005

TEC 2005

To reserver

The reserver

Th All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

## **Foreword**

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 2 to ISO/IEC 13818-4:2004 was prepared by Nornt Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee SC 29, Coding of audio, picture, multimedia and hypermedia information.

# Information technology — Generic coding of moving pictures and associated audio information —

# Part 4:

# **Conformance testing**

AMENDMENT 2: Additional audio conformance test sequences

In clause 2 (Normative references), add:

ISO/IEC 14496-3, Information technology — Coding of audio-visual objects — Part 3: Audio

ISO/IEC 14496-4, Information technology — Coding of audio-visual objects — Part 4: Conformance testing

In subclause 7.4.2 (Descriptions of the audio test bitstreams), replace:

Compressed bitstreams are provided, according to ISO/IEC 13818-3. Detailed descriptions of the bitstreams are furnished below. The following file name extensions are used to identify different parts

testXX.mpg: MPEG-2 audio bitstream

testXX.ext: MPEG-2 audio extension bitstream (optional)

testXX.txt: description file

where XX stands for the bitstream number as indicated in tables 2-4 through 2-7.

with:

Compressed bitstreams are provided according to ISO/IEC 13818-3. Detailed descriptions of the bitstreams are furnished below. The following file name extensions are used:

I?-testXX.txt: description file

I?-testXX.mpg: MPEG-2 audio bitstream

I?-testXX.ext: MPEG-2 audio extension bitstream (optional)
I?-testXX.pcm MPEG-2 audio reference waveform (raw)
I?-testXX.wav MPEG-2 audio reference waveform (wav format)

? stands for the layer (1, 2 or 3)

XX stands for the bitstream number as indicated in tables 2-4 through 2-8.

In subclause 7.4.2 (Descriptions of the audio test bitstreams), add to Table 4:

FEATURE	BIT STREAM NUMBER	
	11	
Layer	II	
matrix	2	
extension	N	
transmission ch alloc	Y	
phantom Centre	N	
prediction	N	
Dyn Cross	N	
Sampling frequency	44.1	
LFE	N	
Multi Lingual	N	
Multi Lingual Fs		.1
ancillary data	N	V.
bitrate BASE stream	384	
bitrate ext. stream	, 00°	
configuration	3/2	

In subclause 7.4.2 (Descriptions of the audio test bitstreams), add to Table 7:

FEATURE	BIT STREAM NUMBER
	32
Layer	II
Sampling frequency	24
bitrate	128
mode	Stereo
ancillary data	N

At the end of subclause 7.4.2 (Descriptions of the audio test bitstreams), add:

Table 7a

bitstream number	mnemonic	layer	signal characteristic	sampling frequency [kHz]	CRC	mode	bitrate [kbit/s]
40	bitrate_16_all	Ш	tonal	16	none	11	all
41	bitrate_22_all	Ш	tonal	22.05	none	11	(all
42	bitrate_24_all	Ш	tonal	24	none	11	all
43	compl24	III	sweep (10 Hz20 kHz, 20 dB)	24	none	110	128
44	Noise	Ш	white noise	22.05	none	00	96
45	IS2	Ш	white noise	22.05	none	01	160
46	MS2	Ш	white noise	22.05	none	01	160
In subclause 8.4.1 (Profile Specification), replace:							

The naming convention for ISO/IEC 13818-7 AAC decoders dictates that a decoder be specified as an A.L.I.D. Channel <Profile Name> Profile ISO/IEC 13818-7 AAC Decoder, where A is replaced by the number of main audio channels, L by the number of LFE channels, by the number of independent coupling channels, D by the number of dependently switched coupling channels, and Profile Name by the actual profile name (Main, Low-Complexity, or Scalable Sampling Rate). An example would be a 5.1.1.1 Channel Main Profile ISO/IEC 13818-7 AAC Decoder, indicating a decoder capable of decoding 5 main audio channels, one LFE channel, one independent coupling channel, and one dependent coupling channel, with each of the channels using the profile specified. This can be abbreviated as M.5.1.1.1. Similarly, a Low Complexity decoder can be specified by a leading "L", and an SSR profile by an "S".

A conforming decoder must support a minimum capability in terms of the number of main audio channels, LFE channels, independent coupling channels, and dependent coupling channels as specified below:

Table 8 - Minimum Decoder Capability for 1, 2, 3, 4, 5, and 7 Main Audio Channels vs. Profile

	Number of Main Audio Channels	Main Profile	Low Complexity	SSR Profile
S		Capability	Profile Capability	Capability
OP	1	1.0.0.0	1.0.0.0	1.0.0.0
	2	2.0.0.0	2.0.0.0	2.0.0.0
	3	3.0.1.0	3.0.0.1	3.0.0.0
	4	4.0.1.0	4.0.0.1	4.0.0.0
	5	5.1.1.1	5.1.0.1	5.1.0.0
	7	7.1.1.2	7.1.0.2	7.1.0.0

## ISO/IEC 13818-4:2004/Amd.2:2005(E)

with:

The naming convention for ISO/IEC 13818-7 AAC decoders can be found in ISO/IEC 13818-3 (ISO/IEC 13818-7:2004, subclause 7.1.4 "Naming Convention for MPEG-2 AAC Decoders and Bitstreams").

A conforming decoder must support a minimum capability in terms of the number of main audio channels, LFE channels, independent coupling channels, and dependent coupling channels as specified in ISO/IEC 13818-3. (ISO/IEC 13818-7:2004, subclause 7.1.5 "Minimum Decoder Capability for Specified Number of Main Audio Channels and Profile"). :200AlAmd 2:

In subclause 8.5.4 (ics\_info()), replace:

Test bitstreams L3 and S17 are provided respectively for Main, Low-Complexity, and Scalable Sampling Rate profiles to test decoder performance on non-meaningful transitions.

with:

Test sequences al03 and as17 are provided respectively for Low-Complexity and Scalable Sampling Rate profiles to test decoder performance on non-meaningfu window sequence transitions (note that Main profile decoders also need to fulfil Low Complexity Profile conformance).

After subclause 8.5.8 (excluded\_channels()), add:

### 8.5.9 SBR

SBR compressed data shall be embedded in accordance with ISO/IEC 13818-7 and the payload shall comply with ISO/IEC 14496-4.

In subclause 8.6 (Procedure to Test Decoder Conformance), replace

The following test procedure applies to all sine sweep signals: Testing is done by comparing the output of a decoder under test with a reference output also supplied by this specification using the procedure described in section 2.6.6.1. Software is provided ...

with:

The following test procedure applies to all sine sweep signals: Testing is done by comparing the output of a decoder under test with a reference output also supplied by this specification using the procedure described in section 2.6.6.1. In cases where the decoder under test is followed by additional operations (e.g. quantizing a signal to a 16 bit output signal) it is permitted to use an intermediate signal output (e.g. with more than 16 bit) for conformance testing. Software is provided ...

In subclause 8.6 (Procedure to Test Decoder Conformance), replace:

For the remaining test sequences, a check of conformance using the LSB oriterion or other measurements (e.g. objective perceptual measurement systems) is not mandatory, but highly recommended. This also applies to bitstreams with non-meaningful window sequences. of ISOILE C

with:

For the remaining AAC-only test sequences, a check of conformance using the LSB criterion or other measurements (e.g. objective perceptual measurement systems) is not mandatory, but highly recommended. This also applies to bitstreams with non-meaningful window sequences.

A decoder implementing the MPEG-2 AAC SBR combination shall comply with a level of the MPEG-4 High Efficiency AAC Profile defined in ISO/IEC 14496-3. Hence, the restrictions and abilities that apply for an MPEG-4 High Efficiency AAC decoder of a certain level also apply for the MPEG-2 AAC SBR decoder of the same capability.

The conformance testing of SBR shall be carried out in accordance to what is specified in ISO/IEC 14496-4. with the exception that all parts relating to any signalling except the implicit signalling shall be ignored.

Furthermore, the same conformance testing and criteria applies for the test-sequences. However, the test sequences are given as ADIF files.

🌃 Annex D (Audio test bitstreams), replace:

This annex lists the bitstream descriptions and bitstream suites that can be used to test audio decoder compliance.

Not all the tests described in subclause 2.5 are covered by these bitstreams, however, some of the fundamental decoder requirements are believed to be covered by these test suites. A compliant decoder is expected to maintain correct audio/visual synchronization while decoding these bitstreams. The tests listed in