

---

---

**Information technology — Coding of  
audio-visual objects —**

**Part 1:  
Systems**

**AMENDMENT 2: Support for raw audio-  
visual data**

*Technologies de l'information — Codage des objets audiovisuels —  
Partie 1: Systèmes*

*AMENDMENT 2: Prise en charge de données audiovisuelles brutes*

IECNORM.COM : Click to view the full PDF of ISO/IEC 14496-1:2010/AMD2:2014



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 2 to ISO/IEC 14496-1:2010 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This Amendment is to define the mechanisms for enabling the use of raw data (audio and video) an MPEG-4 scene. It consists in defining the *ObjectTypeIndication*, the *DecoderSpecificInfo* and the *Access Unit* for *RawVideo* and *RawAudio*.

IECNORM.COM : Click to view the full PDF of ISO/IEC 14496-1:2010/AMD2:2014

# Information technology — Coding of audio-visual objects —

## Part 1: Systems

### AMENDMENT 2: Support for raw audio-visual data

In Table 1, replace line:

|           |                      |
|-----------|----------------------|
| 0x6A-0xBF | Reserved for ISO use |
|-----------|----------------------|

with lines:

|           |                                     |
|-----------|-------------------------------------|
| 0x6A-0x92 | Reserved for Registration Authority |
| 0x93-0xBF | Reserved for ISO use                |

In Table 2, replace line:

|           |                                 |
|-----------|---------------------------------|
| 0x09-0xBF | Reserved for ISO (command tags) |
|-----------|---------------------------------|

with lines:

|           |                                     |
|-----------|-------------------------------------|
| 0x09-0x63 | Reserved for Registration Authority |
| 0x64-0xBF | Reserved for ISO (command tags)     |

In Table 5, replace line:

|           |                      |
|-----------|----------------------|
| 0x09-0x1F | reserved for ISO use |
|-----------|----------------------|

with lines:

|           |   |
|-----------|---|
| 0x09      | LASer stream (defined in ISO/IEC 14496-20:2008, clauses 6 and 12) |
| 0x0A      | SAF stream (defined in ISO/IEC 14496-20:2008, clause 7)           |
| 0x0B      | Raw video stream  |
| 0x0C      | Raw audio stream  |
| 0x0D-0x1F | reserved for ISO use  |

In Table 6, replace:

|             |                      |
|-------------|----------------------|
| 0x0C - 0x1F | reserved for ISO use |
|-------------|----------------------|

with:

|             |                                     |
|-------------|-------------------------------------|
| 0x0C        | Application Multiplex Stream        |
| 0x0D - 0x5B | reserved for Registration Authority |
| 0x5C - 0x1F | reserved for ISO use                |

In 7.2.6.7.2, add the following new paragraph at the end of the subclause:

For values of `DecoderConfigDescriptor.objectTypeIndication` that refer to streams complying with ISO/IEC 14496-20, the decoder specific information is a `LASeRHeader()` defined in 12.2.1 of ISO/IEC 14496-20:2008.

### RAW Video Decoder Specific Info

```
class RAWVideoConfig extends DecoderSpecificInfo : bit(8) tag=DecSpecificInfoTag {
unsigned int(16)    width;
unsigned int(16)    height;
unsigned int(8)     bit_depth;
unsigned int(32)    stride;
unsigned int(32)    coding4CC;
unsigned int(8)     fps;
unsigned int(1)     use_frame_packing;
unsigned int(7)     frame_packing;
}
```

Semantics:

|                   |  |
|-------------------|--|
| width             | – width of the video of the largest color component  |
| height            | – height of the video of the largest color component   |
| bit_depth         | – number of bits for each channel sample from the set of permitted values as defined by coding4CC  |
| stride            | – size in bytes of one horizontal line   |
| coding4CC         | – a 4 character code representing the parameters of the raw data as specified by the MPEG-4 Registration Authority ( <a href="http://www.mp4ra.org/">http://www.mp4ra.org/</a> ) |
| fps               | – frames per second of the video stream; if 0 then the frame rate is not known or variable   |
| use_frame_packing | – this indicates if a frame contains two or more views   |
| frame_packing     | – framePacking as defined in ISO/IEC 23001-8, Coding Independent Code Points   |

**Note** For more than one view the data is packed in a single frame (it is assumed that all views are sampled at the same instant). The packaging is indicated by the `frame_packing` field.

**Example**

```
<decSpecificInfo>
<RAWVideoConfig width=480 height=800 bits_per_pixel=12 stride=720 colorFOURCC="NV21" fps=15
use_frame_packing=1 frame_packing=4 />
</decSpecificInfo>
```

**Note** NV21 is just an example codingFOURCC value.

### RAW Audio Decoder Specific Info

```
class RAWAudioConfig extends DecoderSpecificInfo : bit(8) tag=DecSpecificInfoTag {
unsigned int(24)    sampling_rate;
unsigned int(16)    bits_per_sample;
unsigned int(8)     channels;
unsigned int(32)    coding4CC;
```