
**Self-propelled machinery for forestry —
Roll-over protective structures —
Laboratory tests and performance
requirements**

*Machines forestières automotrices — Structures de protection au
retournement — Essais de laboratoire et exigences de performance*

STANDARDSISO.COM : Click to view the full PDF of ISO 8082:2003



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 8082:2003

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	1
4 Static laboratory tests	3
5 Performance requirements	9
6 Reporting results	11
Annex A (normative) Test report for ISO 8082	13
Bibliography	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8082 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 15, *Machinery for forestry*.

This second edition cancels and replaces the first edition (ISO 8082:1994), which has been technically revised.

Introduction

Special forestry machinery needs a roll-over protective structure (ROPS) standard of its own that specifies the relevant machine types from the enormous variety of forestry machines.

The requirement levels and testing procedures of this International Standard are the same as those of ISO 3471 [1]. In this revised edition, longitudinal loading has been included in the test procedure, the machine types to which the tests are applicable have been specified, and a new bolt and nut class, as well as the – 20 degrees temperature class for Charpy V-notch impact strength, have been added. Specification of the vertical loading beam width also improves the repeatability of the test between different testing laboratories.

STANDARDSISO.COM : Click to view the full PDF of ISO 8082:2003

Self-propelled machinery for forestry — Roll-over protective structures — Laboratory tests and performance requirements

1 Scope

This International Standard establishes a consistent, reproducible means of evaluating the force-deflection characteristics of roll-over protective structures (ROPS) on self-propelled forestry machines under static loading, and prescribes performance requirements for a representative specimen under such loading. It is applicable to forwarders, skidders, feller-bunchers, processors, harvesters and loaders, as defined in ISO 6814. It is not applicable to machines having a rotating platform with a cab and boom on the platform.

NOTE Research work is being done to develop a test method and criteria for machines having a rotating platform with a cab and boom on the platform. These machines are to be included in a future revision of ISO 8082.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 148, *Steel — Charpy impact test (V-notch)*

ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs*

ISO 898-2:1992, *Mechanical properties of fasteners — Part 2: Nuts with specified proof load values — Coarse thread*

ISO 3164, *Earth-moving machinery — Laboratory evaluations of protective structures — Specifications for deflection-limiting volume*

ISO 6814, *Machinery for forestry — Mobile and self-propelled machinery — Terms, definitions and classification*

3 Terms, definitions and symbols

For the purposes of this document, the following terms, definitions and symbols (see Table 1) apply.

3.1

roll-over protective structure

ROPS

system of structural members whose primary purpose is to reduce the possibility of a seat-belted operator being crushed should the machine roll over

NOTE These structural members include any subframe, bracket, mounting, socket, bolt, pin, suspension or flexible shock absorber used to secure the system to the machine frame, but exclude mounting provisions that are integral with the machine frame.

3.2

deflection-limiting volume

DLV

orthogonal approximation of a large, seated, male operator as defined in ISO 3411 wearing normal clothing and a protective helmet

3.3

falling-object protective structure

FOPS

system of structural members arranged in such a way as to provide operators with reasonable protection from falling objects (e.g. trees, rocks)

3.4

operator protective structure

OPS

system of structural members arranged in such a way as to minimize the possibility of operator injury from penetrating objects (such as whipping saplings, branches and broken winch lines)

3.5

simulated ground plane

SGP

flat surface on which, after rolling, a forestry machine is assumed to come to rest

3.5.1

lateral simulated ground plane

LSGP

for a machine coming to rest on its side, the plane 15° away from the DLV about the horizontal axis within the plane established in the vertical plane passing through the outermost point

See Figure 1.

NOTE The LSGP is established on an unloaded ROPS and moves with the member to which load is applied while maintaining its 15° angle with respect to the vertical.

3.5.2

vertical simulated ground plane

VSGP

(rollbar ROPS) for a machine coming to rest in an upside-down position, the plane defined by the top cross-member of the ROPS and that front (or rear) part of the machine likely to come in contact with flat ground at the same time as the ROPS and capable of supporting the upside-down machine

NOTE The VSGP moves with the deformed ROPS.

3.6


machine mass

m

maximum mass declared by the manufacturer, including attachments in the operating condition and with tools, ROPS and all reservoirs filled, but excluding towed equipment (e.g. chippers, planters, discs) and any load that could be carried on the machine

Table 1 — Symbols

Symbol	Description	Unit
U	Energy absorbed by the structure, related to machine mass	J
F	Force	N
m	Machine mass	kg
Δ	Deflection of ROPS	mm

**Key**

- 1 upper ROPS member to which the lateral load is applied
- 2 outermost point from the end view of member (1)
- 3 vertical line through point (2)
- 4 vertical plane parallel to the machine longitudinal centreline through line (3)
- 5 lateral simulated ground plane

Figure 1 — Determination of lateral simulated ground plane (LSGP)**4 Static laboratory tests**

CAUTION — Some of the tests specified in this International Standard involve the use of processes which could lead to a hazardous situation.

4.1 Facilities

Facilities for securing the ROPS/machine frame assemble to the bedplate, as specified in the following, and for applying lateral, longitudinal and vertical loads, shall be provided.

The DLV and its location shall be in accordance with ISO 3164. The DLV shall be fixed firmly to the same part of the machine to which the operator's seat is normally secured, and shall remain there during the entire formal test period. For machines with a reversible operator's position, the DLV is to be considered as the combined clearance zones for the two positions.

4.2 Instruments

The test apparatus shall be equipped with instruments for measuring the force applied to the protective structure and the deflection (deformation) of the structure. The instrument accuracy shall be in accordance with Table 2.

Table 2 — Instrument accuracy requirements

Measurement	Accuracy ^a
Deflection of ROPS	± 5 % of maximum deflection measured
Force applied to ROPS	± 5 % of maximum force measured
^a The percentages are nominal ratings of the accuracy of the instrumentation and shall not be taken to indicate that compensating overtest is required.	

4.3 Apparatus

4.3.1 General

4.3.1.1 Assembly of ROPS to machine frame

The ROPS shall be attached to the machine frame or body as it would be on an operating machine. A complete machine is not required for the evaluation: however, the machine frame or body and ROPS mounting shall represent an operating installation. All normally detachable windows, panels, doors and other non-structural elements shall be removed so that they neither contribute to, nor detract from, the structural evaluation.

4.3.1.2 ROPS/machine attachment to bedplate

The ROPS/machine-frame assembly shall be secured to the bedplate so that the members connecting the assembly and bedplate experience minimal deflection during testing. During lateral loading, the ROPS/machine-frame assembly shall not receive any support from the bedplate, other than that due to the initial attachment.

Connections to the bedplate shall be directly from the machine frame at or near the front-axle support and the rear drive support. For articulated machines, if both frames are used in the evaluation, the hinge shall be locked so that the frames are in a straight line. If the frame on which the ROPS is mounted is used alone, the connections shall be at or near the extreme ends of the frame (see Figure 2).

4.3.1.3 Elimination of energy absorbers

The assembly shall be secured or modified or both so that any machine element that might be considered as suspension (rubber, gas, gas-oil or mechanical spring) shall be effectively eliminated as an energy absorber. However, the ROPS-structural members may include suspension or flexible shock absorbers, which shall not be altered.

4.3.2 Vertical loading

For vertical loading, there is no limitation on securing or supporting the ROPS/machine-frame assembly, except that no repair or straightening of the assembly shall be carried out.




Figure 2 — Machine attachment to bedplate

4.4 Test procedures

4.4.1 General

The test procedures shall consist of the operations specified in 4.4.2, 4.4.3 and 4.4.4, carried out in the order given.

No repair or straightening of any ROPS/machine member shall be carried out during or between the lateral, vertical and longitudinal loading.

NOTE The figures referred to are illustrative and not intended to restrict the design of loading devices.

4.4.2 Lateral loading

4.4.2.1 The force-deflection characteristics shall be determined by lateral loading of the top major longitudinal members of the ROPS.


4.4.2.2 For a ROPS having more than two posts, the lateral loading shall be applied through a load-distribution device having a length not greater than 80 % of the horizontal distance, L , between the front and rear posts of the ROPS (see Figure 3). In the case of curved structural members, the load-distribution device may be attached to the ROPS but shall not have any effect on the strength of the ROPS.

4.4.2.3 For all one- or two-post ROPS, initial loading shall be dictated by the length, L , and the vertical projections of the front and rear planes of the DLV. The load application point may not be within $L/3$ of the ROPS structure. Should the $L/3$ point be between the vertical projection of the DLV and the ROPS structure, the load application point shall be moved away from the structure until it enters the vertical projection of the DLV (see Figure 4).

4.4.2.4 The initial direction of loading shall be horizontal and perpendicular to a vertical plane through the machine's longitudinal centreline. As loading continues, the ROPS/machine-frame deformations can cause the direction of loading to change: this is permissible.

4.4.2.5 If the operator's seat is off the machine's longitudinal centreline, the loading shall be against the outermost side nearest the seat. For on-centreline seats, if mounting of the ROPS is such that different force-deflection relations are obtained from loading from left or right, the side loaded shall be that which will place the most severe requirements on the ROPS/machine assembly.

Dimensions in millimetres

**Key**

- 1 socket
- 2 load distributor


NOTE 1 The load distributor and socket are to prevent local penetration and to hold the end of the load-generating device.

NOTE 2 Typical, but not mandatory, layout.

Figure 3 — Load-distribution device for ROPS with four-post system

4.4.2.6 The rate of application of deflection (load) shall be such that it can be considered static, i.e. a speed of < 5 mm/s. At deflection increments no greater than 15 mm at the point of application of the resultant load, the force and deflection shall be recorded and plotted. The loading shall be continued until the ROPS has achieved both the force and energy requirements. The area under the resulting force–deflection curve equals the energy (see Figure 5). The deflection or deflections used in calculating energy shall be that of the ROPS along the line(s) of action of the force(s). Any deflection of members used to support load-application devices shall not be included in deflection measurements used for the calculation of energy.


Dimensions in millimetres



Key

- 1 socket
- 2 load distributor
- 3 locating axis (LA) of DLV

Figure 4 — Load-distribution device for ROPS with two-post system



Energy:

$$U = \frac{\Delta_1 F_1}{2} + (\Delta_2 - \Delta_1) \frac{F_1 + F_2}{2} + \dots + (\Delta_N - \Delta_{N-1}) \frac{F_{N-1} + F_N}{2}$$

Figure 5 — Force-deflection curve for lateral loading

4.4.3 Vertical loading

4.4.3.1 After removal of the lateral load, a vertical load shall be applied to the top of the ROPS using a 250 mm wide beam (see Figure 6).

4.4.3.2 For ROPS with a two-post system and ROPS with more than two posts, the vertical load shall be applied in the same plane as the lateral loading.

4.4.3.3 For machinery with a reversible operator's position, the load shall be applied midway between the two seat index points.





Figure 6 — Vertical load distribution and loading

4.4.4 Longitudinal loading

4.4.4.1 After removal of the vertical load, a longitudinal load shall be applied to the upper structural members of the ROPS along the longitudinal centreline of the ROPS. It shall be applied at the deformed location of the originally established point, since the lateral (and vertical) loading of the ROPS is likely to result in permanent deformation of the structure. The originally established point is determined by the location of the load distributor and socket prior to any test being performed on the structure.

4.4.4.2 The load distribution device may span the width in cases where no rear (or front) cross-member exists. In all other cases, the device shall not distribute the load over a length greater than 80 % of the width, W , of the ROPS (see Figure 7). No ROPS, straight or curved, should have its strength affected by the load distributor.

Dimensions in millimetres

**Key**

- 1 socket
- 2 load distributor

NOTE 1 The load distributor and socket are to prevent local penetration and to hold the end of the load-generating device.

NOTE 2 Typical, but not mandatory, layout.

^a Parallel to longitudinal centreline of machine.

Figure 7 — Longitudinal loading

4.4.4.3 The direction of loading (fore or aft) shall be selected to place the most severe requirements on the ROPS/machine-frame assembly. The initial direction of loading shall be horizontal and parallel to the original longitudinal centreline of the machine. Some additional factors to consider in deciding on the direction to apply the longitudinal load are

- a) the location of the ROPS relative to the DLV and the effect that longitudinal deflection of the ROPS would have on providing crush protection for the operator,
- b) machine characteristics (e. g. other structural members of the machine which may resist longitudinal deflection of the ROPS) that can limit direction of the longitudinal component of loading on the ROPS, and
- c) experience which may indicate the possibility of longitudinal tipping or the tendency of a particular classification of machine to skew as it rotates about a longitudinal axis during an actual roll-over.

4.4.4.4 The rate of deflection shall be such that the loading may be considered static (see 4.4.2.6). This loading is to continue until the ROPS has achieved the force requirement or requirements.

5 Performance requirements

5.1 General

During each test, no part of the ROPS shall enter the DLV of the operator (see ISO 3164). For machinery with a reversible operator's position, the load shall be applied midway between the two seat index points. Deformation of the ROPS shall not allow the simulated ground plane to enter this zone.

5.2 Force-energy and load requirements

5.2.1 These requirements shall be met within the deflection or deflections permitted by the deflection-limiting volume in accordance with ISO 3164. The requirements are related to the machine mass, m .

5.2.2 The lateral load force attained shall be at least that specified for the corresponding machine type in Table 3.

The force and energy requirements need not be attained simultaneously. If the required force is attained or exceeded before the energy requirement is met, the force may decrease, but shall again attain the required force when the energy is achieved or exceeded.

Table 3 — Minimum force attained during lateral loading

Machine type	Force F N
Wheeled forestry machines ^a	$F = 60\,000 \left(\frac{m}{10\,000} \right)^{1,2}$
Track-laying forestry machines	$F = 70\,000 \left(\frac{m}{10\,000} \right)^{1,2}$
^a Includes machines where the tracks can be mounted on rubber tyres as optional equipment.	

5.2.3 The energy absorbed during lateral loading shall be at least that specified for the corresponding machine type in Table 4.

Table 4 — Minimum energy absorbed during lateral loading

Machine type	Energy U J
Wheeled forestry machines ^a	$U = 12\,500 \left(\frac{m}{10\,000} \right)^{1,25}$
Track-laying forestry machines	$U = 13\,000 \left(\frac{m}{10\,000} \right)^{1,25}$
^a Includes machines where the tracks can be mounted on rubber tyres as optional equipment.	

5.2.4 After removal of the lateral load, the ROPS/machine assembly shall support a vertical load of $20 \times m$, expressed in newtons, for a period of 5 min or until any deformation has ceased, whichever is the shorter.

5.2.5 The longitudinal load force attained shall be at least that specified for the corresponding machine type in Table 5.

Table 5 — Minimum force attained during longitudinal loading

Machine type	Force F N
Wheeled forestry machines ^a	$F = 48\,000 \left(\frac{m}{10\,000} \right)^{1,2}$
Track-laying forestry machines	$F = 56\,000 \left(\frac{m}{10\,000} \right)^{1,2}$
^a Includes machines where the tracks can be mounted on rubber tyres as optional equipment.	

5.3 Temperature and material requirements

5.3.1 General

The laboratory evaluations should be performed with all ROPS and machine-frame members soaked to temperature – 18 °C or below. If the evaluations are not performed at this temperature, the minimum material requirements in 5.3.2 and 5.3.3 shall be met.

5.3.2 Bolts and nuts

Bolts and nuts used to attach the ROPS to the machine frame and to connect structural parts of the ROPS shall be

- property class 8.8, 9.8 or 10.9 for bolts (see ISO 898-1), and
- property class 8, 9 or 10 for nuts (see ISO 898-2).

5.3.3 Impact strength

The structural members of the ROPS and the mounts which attach it to the machine shall be made of steel having a Charpy V-notch impact strength in accordance with Table 6.

Specimens are to be “longitudinal” and taken from flat stock, tubular or structural sections before forming or welding for use in the ROPS. Specimens from tubular or structural sections shall be taken from the middle of the side of greatest dimensions and shall not include welds (see ISO 148).

6 Reporting results

The results of the tests shall be reported using a test report in accordance with Annex A.