

DIGLYCIDYL ESTER RESIN

1. SCOPE:

- 1.1 Form: This specification covers a prepolymer in the form of a low molecular weight aromatic diglycidyl ester resin.
- 1.2 Application: Primarily for use in manufacture of composite matrices.
- 1.3 Safety - Hazardous Materials: While the materials, methods, applications, and processes described or referenced in this specification may involve the use of hazardous materials, this specification does not address the hazards which may be involved in such use. It is the sole responsibility of the user to ensure familiarity with the safe and proper use of any hazardous materials and to take necessary precautionary measures to ensure the health and safety of all personnel involved.

2. APPLICABLE DOCUMENTS: The following publications form a part of this specification to the extent specified herein. The latest issue of Aerospace Material Specifications shall apply. The applicable issue of other documents shall be as specified in AMS 2350.

- 2.1 SAE Publications: Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

2.1.1 Aerospace Material Specifications:

AMS 2350 - Standards and Test Methods
AMS 2825 - Material Safety Data Sheets

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

AMS documents are protected under United States and international copyright laws. Reproduction of these documents by any means is strictly prohibited without the written consent of the publisher.

2.2 ASTM Publications: Available from American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

ASTM D1652 - Epoxy Content of Epoxy Resins

ASTM D1726 - Hydrolyzable Chloride Content of Liquid Epoxy Resins

ASTM D1763 - Epoxy Resins

ASTM D2393 - Viscosity of Epoxy Resins and Related Components

2.3 U.S. Government Publications: Available from Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

2.3.1 Military Standards:

MIL-STD-794 - Parts and Equipment, Procedures for Packaging and Packing of

3. TECHNICAL REQUIREMENTS:

3.1 Material: Shall be a low molecular weight, aromatic diglycidyl ester resin partially derived from phthalic anhydride reacted with epichlorohydrin to form first diglycidyl phthalate and subsequently a polyepoxide.

3.2 Impurities: Resin shall be substantially free of foreign matter and shall contain not more than 1% hydrolyzable chlorine, determined in accordance with ASTM D1726.

3.3 Properties: Resin shall conform to the following requirements, determined in accordance with specified ASTM methods:

3.3.1 Epoxy Content (equiv. per 100 g) 0.556 - 0.667 ASTM D1652

3.3.2 Viscosity at 25°C (77°F), cps 600 - 1800 ASTM D2393

3.4 Quality: The resin, as received by purchaser, shall be uniform in quality and condition, clean, and free from foreign materials and from contaminants detrimental to usage of the resin.

4. QUALITY ASSURANCE PROVISIONS:

4.1 Responsibility for Inspection: The vendor of the resin shall supply all samples for vendor's tests and shall be responsible for performing all required tests. Results of such tests shall be reported to the purchaser as required by 4.5. Purchaser reserves the right to sample and to perform any confirmatory testing deemed necessary to ensure that the resin conforms to the requirements of this specification.

4.2 Classification of Tests: Tests to determine conformance to all technical requirements of this specification are classified as acceptance tests and as preproduction tests and shall be performed prior to or on the initial shipment of resin to a purchaser, on each lot, when a change in material, processing, or both requires reapproval as in 4.4.2, and when purchaser deems confirmatory testing to be required.

4.3 Sampling: Shall be as follows:

4.3.1 For Acceptance Tests: Each lot of resin shall be sampled at random to provide sufficient resin to perform all required tests. The number of determinations for each requirement shall be as specified in the applicable test procedure, or, if not specified therein, not less than three.

4.3.1.1 A lot shall be all resin produced in a continuous production run from the same batches of raw materials under the same fixed conditions and presented for vendor's inspection at one time. A lot may be packaged in small quantities and delivered under the basic lot approval provided lot identification is maintained.

4.3.1.2 A batch shall be the quantity of material run in a reactor or mixer at one time.

4.3.1.3 When a statistical sampling plan and acceptance quality level (AQL) have been agreed upon by purchaser and vendor, sampling shall be in accordance with such plan in lieu of sampling as in 4.3.1 and the report of 4.5.1 shall state that such plan was used.

4.3.2 For Preproduction Tests: As agreed upon by purchaser and vendor.

4.4 Approval:

4.4.1 Sample resin shall be approved by purchaser before resin for production use is supplied, unless such approval be waived by purchaser. Results of tests on production resin shall be essentially equivalent to those on the approved sample.

4.4.2 Vendor shall use ingredients, manufacturing procedures, processes, and methods of inspection on production resin which are essentially the same as those used on the approved sample resin. If necessary to make any change in ingredients, in type of equipment for processing, or in manufacturing procedures, vendor shall submit for reapproval a statement of the proposed changes in material, processing, or both and, when requested, sample resin. Production resin made by the revised procedure shall not be shipped prior to receipt of reapproval.

4.5 Reports:

4.5.1 The vendor of resin shall furnish with each shipment a report showing the results of tests to determine conformance to the technical requirements of this specification. This report shall include the purchase order number, AMS 3296, vendor's product designation, lot number, date of manufacture, and quantity.

- 4.5.1.1 A material safety data sheet conforming to AMS 2825, or equivalent, shall be supplied to each purchase prior to, or concurrent with, the report of preproduction test results or, if preproduction testing be waived by purchaser, concurrent with the first shipment of resin for production use. Each request for modification of resin formulation shall be accompanied by a revised data sheet for the proposed formulation.
- 4.5.2 The vendor of finished or semi-finished parts shall furnish with each shipment a report showing the purchase order number, AMS 3296, contractor or other direct supplier of resin, vendor's product designation, part number, and quantity. When resin for making parts is produced or purchased by the parts vendor, that vendor shall inspect each lot of resin to determine conformance to the requirements of this specification and shall include in the report either a statement that the resin conforms or copies of laboratory reports showing the results of tests to determine conformance.
- 4.6 Resampling and Retesting: If any specimen used in the above tests fails to meet the specified requirements, disposition of the resin may be based on the results of testing three additional specimens for each original nonconforming specimen. Failure of any retest specimen to meet the specified requirements shall be cause for rejection of the resin represented and no additional testing shall be permitted. Results of all tests shall be reported.

5. PREPARATION FOR DELIVERY:

5.1 Identification and Packaging:

- 5.1.1 The resin shall be packaged in air-tight containers and stored away, or otherwise protected, from excessive heat and humidity. Type and size of containers shall be as agreed upon by purchaser and vendor.
- 5.1.2 Each container of resin shall be identified with an attached label using characters of such size as to be legible and which will not be obliterated by normal handling. Each label shall show not less than the following information:

DIGLYCIDYL ESTER RESIN

AMS 3296

MANUFACTURER'S IDENTIFICATION _____

PURCHASE ORDER NUMBER _____

DATE OF MANUFACTURE _____

LOT NUMBER _____

QUANTITY _____

STORE AWAY FROM EXCESSIVE HEAT AND HUMIDITY