



AEROSPACE RECOMMENDED PRACTICE

ARP908™**REV. D**

Issued	1968-01
Revised	1988-11
Reaffirmed	2013-01
Stabilized	2023-11

Superseding ARP908C

Torque Requirements, Installation and Qualification Test, Hose and Tube Fitting

RATIONALE

This technical report is being stabilized because it covers technology, products, or processes which are mature and not likely to change in the foreseeable future.

STABILIZED NOTICE

This document has been declared "STABILIZED" by SAE G-3, Aerospace Couplings, Fittings, Hose, Tubing Assemblies Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of arp908d

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2023 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

For more information on this standard, visit
<https://www.sae.org/standards/content/ARP908D/>

1. SCOPE:

- Ø This Aerospace Recommended Practice (ARP) is intended to establish recommended installation torque value limits and test criteria for machined flared and flareless hose and tube end fitting connections. Assembly of bite-type MS21922 flareless sleeves is not included in this ARP (see MIL-F-18280).

This ARP is applicable to two types of connections and two basic material classifications.

Type I - Flared to mate with MS33656
Type II - Flareless to mate with MS33514

- Ø Material I - Steel, corrosion resistant steel, and titanium fittings
Material II - Aluminum fittings

2. INSTALLATION TORQUE:

Hose and tube fittings should be assembled with a torque per values established for the material being installed. When any component of the joint (for example, nipple or fitting end) is aluminum, the values for Material II shall apply.

3. REPEATED TORQUE TEST:

When qualification testing, at least two fittings of the type and material to be qualified shall be tested as follows:

SAENORM.COM : Click to view the full PDF of arp908d

3.1 Repeated Assembly Test: Specimens shall be screwed together and unscrewed eight times. Each of the eight cycles shall include the complete removal of the fitting from the test manifold union. Fitting nuts shall be tightened to the torques specified in Table 1, one half shall be tightened to the minimum, one half to the maximum tightening torque. Following the first, fourth and eighth installation, proof tests shall be conducted. Following the eighth installation the fittings shall be placed in a protective enclosure and pressure tested with nitrogen and examined under water for 5 min at the nominal rated (system) pressure. There shall be no leakage and the fitting nut shall remain free to swivel by hand after the final disassembly.

3.1.1 Lubrication: All adapter to fitting threads and contact surfaces shall be lubricated with MIL-H-5606 oil prior to application of torque.

It is noted that MIL-H-5606 oil is not compatible with all systems and is not, therefore, used as a universal lubricant. However, for purposes of consistency of testing, all qualification testing will be performed with MIL-H-5606. Use of other lubricants is permitted in systems, but torques may have to be adjusted accordingly. In no case should the fittings be assembled totally dry and without lubricants on all bearing surfaces.

3.1.2 Application of Torque: The fittings being qualified shall be assembled on a mating fitting of the same material classification and having end configurations in accordance with drawings MS33656 or MS33514 as applicable. The fitting nut shall be tightened to the appropriate torque value per 3.1 and Table 1 for each size and material and loosened. The hose nipple on hose assemblies and machined sleeve ends on tube assemblies should be restrained while applying torque to the components to prevent galling of the sealing surfaces. (When any component of the joint (that is, nipple, nut or fitting end) is aluminum, the values for Material II shall apply.) It is recommended that an adjustable (break-over) torque handle be used. This test applies to the machined, flared and flareless type ends.