


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

REV. A	FEDERAL SUPPLY CLASS 5305	
	NOTICE THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION AN116961 THRU AN117000 REV. 2, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE AN116961 THRU AN117000 REV. 2, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED. THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT. UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.	
AS116961 THRU AS117000	SAENORM.COM : Click to view the full PDF of as116961	
 SAE 100 <i>Leading Our World In Motion</i>		THIRD ANGLE PROJECTION 
PREPARED BY SAE COMMITTEE E-25		PROCUREMENT SPECIFICATION: NONE
 SAE Aerospace <i>An SAE International Group</i>	AEROSPACE STANDARD SCREW - OVAL FILLISTER DRILLED HEAD, .138-32	AS116961 THRU AS117000 SHEET 1 OF 3
		REV. A




FIGURE 1

TABLE 1

L	K +.000 -.060	PART NO.	L	K +.000 -.060	PART NO.	L	K +.000 -.060	PART NO.
.250	(a)	AN116962	.938	(a)	AN116973	2.750	1.500	MS116988
.312	(a)	AN116963	1.000	(a)	AN116974	3.000	1.750	MS116990
.375	(a)	AN116964	1.125	(a)	AN116975			
.438	(a)	AN116965	1.250	(a)	AN116976			
.500	(a)	AN116966	1.375	.125	AN116977			
.562	(a)	AN116967	1.500	.250	AN116978			
.625	(a)	AN116968	1.625	.375	AN116979			
.688	(a)	AN116969	1.750	.500	AN116980			
.750	(a)	AN116970	1.875	.625	AN116981			
.812	(a)	AN116971	2.000	.750	AN116982			
.875	(a)	AN116972	2.250	1.000	AN116984			
			2.500	1.250	AN116986			

(a) THREAD IS HEAD. MAX TWO IMPERFECT THREADS.

NOTE: SHANK SHALL BE STRAIGHT WITHIN .004 FIR. PER INCH OF SCREW LENGTH.

THE CONCENTRICITY OF THREAD PD IN RELATION TO THE HEAD SHALL BE WITHIN .005 FIR.

MATERIAL: STEEL AMS 5061

STRESS RELIEVE AFTER HEADING. MATERIAL SPECIFICATION HARDNESS REQUIREMENTS MUST BE MAINTAINED.