LOCATION OF IDENTIFICATION /5/ (T2) øс FITTING END PER ASIO98 STYLE G SEAL RING PER AS1097 /6/ 15° TO ØE FITTING END PER MS33649 EXCEPT AS NOTED (TI)ENLARGED VIEW A

FIGURE 1 - BUSHING SCREW THREAD REDUCER

√ABLE 1 - DIMENSIONS

BASIC		·: 64					
NUMBER		THREAD END		TUBE END			
AS4340	INTERNAL	T1 THREAD	FLARED	T2 THREAD	Α		
/12/	TUBE	PER	TUBE	PER	+.000		
SIZE CODE	OD 🦯	MIL-S-8879	OD	MIL-S-8879	032	В	С
0408	. 250	.4375-20 UNJF	. 500	.7500-16 UNJF	1.016	. 609	.168175
0612	375	.5625-18 UNJF	.750	1.0625-12 UNJ	1.266	. 609	.293301
0812	500	.7500-16 UNJF	.750	1.0625-16 UNJ	1.641	.734	.387395
0816	. 500	.7500-16 UNJF	1.000	1.3125-12 UNJ	1.688	.734	.387395
1216	. 750	1.0625-12 UNJ	1.000	1.3125-12 UNJ	1.922	.922	.604614

THIRD ANGLE PROJECTION

REAFFIRMED 2001-12

ISSUED

Printed in the U.S.A.

PROCUREMENT SPECIFICATION: /4/ KSC-F-124 CUSTODIAN: SAE G-3/G-3B

The Engineering Society
For Advancing Mobility
Land Sea Air and Space

AEROSPACE STANDARD

BUSHING - SCREW THREAD REDUCER, FOR SEAL RING

AS4340

SHEET 1 OF 2