

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
A

SAE AS4882

FEDERAL SUPPLY CLASS
5340

RATIONALE

AS4882A HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.





FIGURE 1 - QUARTER TURN QUICK RELEASE CLAMP

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS4882A>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3E

PROCUREMENT SPECIFICATION: NONE

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

CLAMP, LOOP, CUSHIONED, HINGED,
QUICK RELEASE - CABLE OR WIRE

SAE AS4882
SHEET 1 OF 4

**REV.
A**

Copyright 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1996-12 REVISED 2003-09 REAFFIRMED 2013-01




FIGURE 2 - VIEW J-J ENLARGED
SHOWING QUARTER TURN LOCKING DEVICE IN UNLOCKED POSITION
CUSHION OMITTED FOR CLARITY




FIGURE 3 - VIEW L-L
SHOWING SLOT IN BRACKET




FIGURE 4 - DEVELOPED FLAT PATTERN
SHOWING LAY OF CUSHION




FIGURE 5 - SECTION K-K ENLARGED
CUSHION ONLY
REMOVE ALL FLASH

TABLE 1 - DIMENSIONS

BASIC NO. AS4882	WORKING DIAMETER RANGE	D ±.015	E ±.030	F	G ±.03	H
SIZE CODE 1/13						
01	.35- .42	.825	.561	1.18	.88	1.84
02	.42- .49	.885	.601	1.26	.91	1.89
03	.49- .57	.955	.632	1.34	.94	1.95
04	.57- .68	1.055	.663	1.38	.99	2.03
05	.68- .80	1.175	.726	1.50	1.06	2.15
06	.80- .93	1.305	.787	1.65	1.13	2.26
07	.93-1.07	1.445	.850	1.77	1.20	2.38
08	1.07-1.21	1.585	.878	1.89	1.27	2.51