

REV.
B

AS6047

RATIONALE

FEDERAL SUPPLY CLASS
4730

FIGURE 1 REDRAWN TO CORRECT RIGHT-HAND VIEW.





FIGURE 1 - FITTING, UNION, STANDARD AND REDUCER, BULKHEAD END,
NON-REDUCER SHOWN

TABLE 1 - OVERALL LENGTH A /9/ /11/

SIZE OF PORT #2	02	03	04	05	06	SIZE OF PORT #1							
	±.010	±.010	±.010	±.010	±.010	08	10	12	14	16	20	24	32
02	1.484	1.516	1.578	1.609	1.703	1.844	2.000	2.156	2.156	2.156	2.156	2.156	2.422
03	1.516	1.563	1.625	1.656	1.750	1.891	2.047	2.203	2.203	2.203	2.203	2.203	2.469
04	1.547	1.594	1.656	1.688	1.781	1.922	2.078	2.234	2.234	2.234	2.234	2.234	2.500
05	1.578	1.625	1.688	1.688	1.781	1.922	2.078	2.324	2.234	2.234	2.234	2.234	2.500
06	1.641	1.688	1.750	1.750	1.797	1.938	2.094	2.250	2.250	2.250	2.250	2.250	2.516
08	1.734	1.781	1.844	1.844	1.891	2.031	2.188	2.344	2.344	2.344	2.344	2.344	2.609
10	1.813	1.859	1.922	1.922	1.969	2.109	2.250	2.406	2.406	2.406	2.406	2.406	2.672
12	1.922	1.969	2.031	2.031	2.078	2.219	2.360	2.484	2.469	2.469	2.469	2.469	2.734
14	1.922	1.969	2.031	2.031	2.078	2.219	2.360	2.469	2.469	2.469	2.469	2.469	2.734
16	1.922	1.969	2.031	2.031	2.078	2.219	2.360	2.469	2.469	2.469	2.469	2.469	2.734
20	1.922	1.969	2.031	2.031	2.078	2.219	2.360	2.469	2.469	2.469	2.469	2.469	2.734
24	1.922	1.969	2.031	2.031	2.078	2.219	2.360	2.469	2.469	2.469	2.469	2.469	2.734
32	1.984	2.031	2.094	2.094	2.141	2.281	2.422	2.531	2.531	2.531	2.531	2.531	2.734

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS6047B>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: /5/ AS18280



AEROSPACE STANDARD

FITTING, UNION,
STANDARD AND REDUCER,
BULKHEAD, FLARELESS, PRECISION TYPE

AS6047
SHEET 1 OF 4

REV.
B

TABLE 2 - HOLE DEPTH Y /9/ /11/

SIZE OF PORT #2	SIZE OF PORT #1												
	02	03	04	05	06	08	10	12	14	16	20	24	32
02	-	-	-	-	-	-	-	-	-	-	-	-	-
03	.469	-	-	-	-	-	-	-	-	-	-	-	-
04	.484	.484	-	-	-	-	-	-	-	-	-	-	-
05	.500	.500	.516	-	-	-	-	-	-	-	-	-	-
06	.547	.531	.562	.562	-	-	-	-	-	-	-	-	-
08	.594	.594	.625	.625	.641	-	-	-	-	-	-	-	-
10	.656	.656	.672	.672	.703	.672	-	-	-	-	-	-	-
12	.719	.719	.734	.750	.766	.750	.750	-	-	-	-	-	-
14	.688	.688	.704	.719	.735	.719	.719	.861	-	-	-	-	-
16	.656	.656	.672	.672	.703	.688	.688	.719	.688	-	-	-	-
20	.594	.594	.609	.609	.641	.625	.625	.656	.625	.703	-	-	-
24	.516	.516	.531	.547	.562	.641	.656	.578	.547	.641	.656	-	-
32	.453	.438	.469	.469	.469	.469	.469	.516	.485	.562	.578	.656	-

TABLE 3 - HOLE DEPTH Z /9/ /11/

SIZE OF PORT #2	SIZE OF PORT #1												
	02	03	04	05	06	08	10	12	14	16	20	24	32
02	-	1.016	1.062	1.078	1.156	1.250	1.391	1.500	1.477	1.438	1.375	1.297	1.438
03	-	-	1.047	1.078	1.141	1.250	1.391	1.500	1.471	1.422	1.375	1.297	1.422
04	-	-	-	1.094	1.172	1.281	1.406	1.516	1.494	1.453	1.391	1.312	1.453
05	-	-	-	-	1.172	1.281	1.422	1.531	1.500	1.453	1.391	1.328	1.453
06	-	-	-	-	-	1.297	1.438	1.547	1.523	1.391	1.422	1.344	1.484
08	-	-	-	-	-	-	1.453	1.562	1.533	1.484	1.438	1.359	1.391
10	-	-	-	-	-	-	-	1.562	1.537	1.500	1.438	1.359	1.500
12	-	-	-	-	-	-	-	-	1.574	1.531	1.468	1.406	1.531
14	-	-	-	-	-	-	-	-	-	1.566	1.503	1.430	1.559
16	-	-	-	-	-	-	-	-	-	-	1.516	1.453	1.562
20	-	-	-	-	-	-	-	-	-	-	-	1.468	1.594
24	-	-	-	-	-	-	-	-	-	-	-	-	-
32	-	-	-	-	-	-	-	-	-	-	-	-	-

TABLE 4 - TUBE SIZE AND CORRESPONDING THREAD

PORT SIZE	(NOMINAL TUBE SIZE)	T THREAD PER AS8879
02	.125	.3125-24 UNJF
03	.188	.3750-24 UNJF
04	.250	.4375-20 UNJF
05	.312	.5000-20 UNJF
06	.375	.5625-18 UNJF
08	.500	.7500-16 UNJF
10	.625	.8750-14 UNJF
12	.750	1.0625-12 UNJ
14	.875	1.1875-12 UNJ
16	1.000	1.3125-12 UNJ
20	1.250	1.6250-12 UNJ
24	1.500	1.8750-12 UNJ
32	2.000	2.5000-12 UNJ



AEROSPACE STANDARD
FITTING, UNION,
STANDARD AND REDUCER,
BULKHEAD, FLARELESS, PRECISION TYPE

AS6047
SHEET 2 OF 4

**REV.
B**

TABLE 5 - HEX DIMENSION AND WEIGHTS /9/ /10/

BASIC NO. AS6047 /19/ LARGEST PORT SIZE CODE	B ±.010	H	LB/EA APPROX REF ALUM	LB/EA APPROX REF STEEL	LB/EA APPROX REF TI
02	.542	.552- .565	.00990	.0279	.0153
03	.605	.615- .628	.0162	.0432	.0243
04	.668	.678- .691	.0207	.0558	.0315
05	.730	.740- .753	.0261	.0702	.0405
06	.792	.802- .815	.0315	.0855	.0486
08	.980	.990-1.003	.0576	.158	.0900
10	1.103	1.113-1.128	.0810	.210	.126
12	1.353	1.363-1.380	.120	.325	.187
14	1.478	1.488-1.505	-	-	-
16	1.603	1.613-1.630	.182	.437	.286
20	1.853	1.863-1.880	.224	.610	.332
24	2.099	2.109-2.225	.266	.733	.422
32	2.724	2.734-2.760	-	-	-

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

/1/ MATERIAL:

- a. CODE LETTER T – TYPE 6AL-4V TITANIUM ALLOY PER PROCUREMENT SPECIFICATION
- b. CODE LETTER V – TYPE 15-5PH, CORROSION RESISTANT STEEL PER PROCUREMENT SPECIFICATION
- c. CODE LETTER W – TYPE 7075-T73 ALUMINUM ALLOY BAR OR FORGING, OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER PROCUREMENT SPECIFICATION

2. HEAT TREATMENT:

- a. MATERIAL CODE LETTER T – ANNEALED PER PROCUREMENT SPECIFICATION
- b. MATERIAL CODE LETTER V – AGE TO CONDITION H1075 PER PROCUREMENT SPECIFICATION
- c. MATERIAL CODE LETTER W – ELECTRICAL CONDUCTIVITY AND HARDNESS PER PROCUREMENT SPECIFICATION

/3/ FINISH:

- a. MATERIAL CODE LETTER T – ANODIZE OR FLUORIDE PHOSPHATE CONVERSION COAT PER PROCUREMENT SPECIFICATION
- b. MATERIAL CODE LETTER V:
 1. V CODE PARTS TO BE PASSIVATED ONLY WILL HAVE NO FINISH CODE LETTER AFTER THE SIZE CODE IN THE PART NUMBER. THE FINISH WILL BE: PASSIVATE PER PROCUREMENT SPECIFICATION.
 2. V CODE PARTS TO BE CADMIUM PLATED ONLY SHALL HAVE THE FINISH CODE LETTER "P" AFTER THE SIZE CODE IN THE PART NUMBER. THE FINISH WILL BE: CADMIUM PLATE PER PROCUREMENT SPECIFICATION.
- c. MATERIAL CODE LETTER W – T73 OR T7351 PER PROCUREMENT SPECIFICATION

/4/ OXYGEN SYSTEM AND COMPONENT CLEANING, SUFFIX LETTER A /19/:

- a. MATERIAL CODE LETTER V – CLEAN AND PACKAGE PER ARP1176 CATEGORY 1C
- b. MATERIAL CODE LETTER W – CLEAN AND PACKAGE PER ARP1176 CATEGORY 2