

**(R) Sound Measurement—Construction Site**

**Foreword**—This Document has also changed to comply with the new SAE Technical Standards Board Format. Definitions have changed to Section 3. All other section numbers have changed accordingly.

**1. Scope**—This SAE Standard sets forth measurement procedures and instrumentation to be used for determining a “representative” sound level during a representative time period at selected measurement locations on a construction site boundary. The document is not intended for use in determining occupational hearing damage risk. Determination of a representative time period is left to the judgment of the user.

**1.1 Purpose**—The purpose of this SAE document is to set forth procedures that may be used by construction site management for self-regulation and construction site planning or by state and local officials for the enforcement of construction site noise regulations. Two measurement methods are provided to obtain the time-integrated equivalent sound level,  $L_{eq}$ , emitted by construction site activity. First, a sampling procedure is recommended for use with a sound level meter. Second, a measurement procedure using an integrating sound level meter is presented. The latter procedure is generally preferred. Use of this document provides sound level data representative of the complex time-varying sounds emitted by construction activities, which may be used to estimate community reaction to the construction activity.

**2. References**

**2.1 Applicable Publications**—The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J184 NOV98—Qualifying a Sound Data Acquisition System

2.1.2 ANSI PUBLICATIONS—Available from ANSI, 11 West 42nd Street, New York, NY 10036-8002.

ANSI S1.4-1983 (R1997) (1997)—Specifications for Sound Level Meters

ANSI S1.4A-1985—Amendment to ANSI S1.4-1983

ANSI S12.9/3 (R1998) (1998)—Quantities and Procedures for Description and Measurement of Environmental Sound, Part 3: Short-term measurement with an observer present

SAE Technical Standards Board Rules provide that: “This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user.”

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

TO PLACE A DOCUMENT ORDER; (724) 776-4970 FAX: (724) 776-0790  
SAE WEB ADDRESS <http://www.sae.org>

2.1.3 IEC PUBLICATION—Available from International Electrotechnical Commission, 3, rue de Verambe, P.O. Box 131, 1211 Geneva 20, Switzerland.

IEC 60651 (1979)—Sound Level Meters

IEC 60804 (1985)—Integrating-Averaging Sound Level Meters, plus amendments

IEC 60942 (1997)—Sound Calibrators

### 3. Definitions

3.1 **Construction Site**—That area within the defined boundaries of the project. This includes defined boundary lines of the project itself, plus any staging area outside those defined boundary lines used expressly for construction or demolition.

3.2 **Construction Site Boundaries**—The outermost limit lines of the construction site.

3.3 **Noise Sensitive Area**—Property such as that used for public, commercial, religious, or educational purposes, or home dwellings, parks, and other special-purpose areas in the vicinity of a construction site where the background sound is less than the construction site sound level.

3.4 **Background Noise**—Total acoustical and electrical noise from all sources in a system that interferes with the production, transmission, detection, measurement, or recording of a signal.

NOTE—In many cases, the acoustical noise is the background sound.

3.5 **Background Sound**—The all-encompassing sound typically associated with the environment in a given area, being composed of sounds from many sources far and near, when the construction site is inactive.

3.6 **Representative Sound Level,  $L_A$** —The average of sound level samples obtained in accordance with the procedures.

3.7 **Equivalent (or Time-Average) Sound Level,  $L_{eq}$** —Equivalent or time-average sound is the square root of the time-average of instantaneous sound pressure squared. It is also termed the root-mean-square sound. Equivalent sound level is 10 times the common logarithm of the square of the ratio of the equivalent or time-average sound to the reference sound,  $p_{0r}$ , of 20  $\mu$ Pa.

### 4. Instrumentation

#### 4.1 Sound Level Measurement Instrument

4.1.1 If 5.1 is to be followed, a sound level meter meeting Type 1 or Type 2 requirements of ANSI S1.4-1983 (R1997) or IEC 60651 (1979) shall be used.

4.1.2 If 5.2 is to be followed, an integrating sound level meter that provides the equivalent sound level for a measurement period of at least 30 min shall be used. The integrating-averaging sound level meter meeting Type 1 or Type 2 requirements of IEC 60804 (1985) (plus amendments No 1 and 2) should be used. The integrating sound level meter shall have a "pause" or "standby" capability which inhibits data collection. The dynamic range of the instrument should be at least 80 dB, including crest factor.

4.1.3 As an alternative to making direct measurements with a sound level meter or integrating sound level meter, a microphone or sound level meter may be used with a magnetic tape recorder or graphic level recorder and data analysis instrumentation providing the system meets the requirements of SAE J184 NOV98.

**4.2 Calibrator**—An acoustic calibrator with an accuracy within  $\pm 0.5$  dB meeting the requirements of IEC 60942-1997.

**4.3 Windscreen**—A microphone windscreen shall be used except when the user is certain that the wind-induced noise is more than 15 dB below the sound level of the source being measured. A windscreen may be used at all times. When a windscreen is used, it shall be of a type recommended by the microphone manufacturer, and it shall not affect the A-weighted sound level of the source being measured by more than  $\pm 0.5$  dB in a calm (no wind) situation.

**4.4 Anemometer**—An anemometer or other device for use in measurement of wind speed and direction with an accuracy within  $\pm 10\%$  at 20 km/h.

## 5. Site Characterization

**5.1** Obtain specific drawings, survey stake locations, or other pertinent information and sketch the boundaries of the construction site and noise sensitive areas; a facsimile of Figure 1 may be used. Note the distance between the noise sensitive area(s) and the nearest boundaries.

**5.2** Obtain information to determine location and activity pattern of equipment on the construction site during the planned measurement period.

**5.3** Based on 5.1 and 5.2, select the sound level measurement location(s).

**6. Measurements**—Two sound level measurement procedures are presented. A manual sampling procedure using a sound level meter is given in 6.1. Paragraph 6.2 describes the procedure for using an integrating-averaging sound level meter.

NOTE—ANSI S12.9/3-1993 (R1998), meets the requirements of this document and provides a more detailed method to measure  $L_{eq}$  corrected for background sound.

**6.1 Manual Sampling with Sound Level Meter**—Sound level measurements at construction site boundary adjacent to noise sensitive areas shall be taken with a sound level meter in the following manner for any representative 30 min period of construction activity:

6.1.1 Calibrate the sound level meter before and after each measurement period using an acoustic calibrator, per manufacturer's instructions. If calibration shifts by more than 0.5 dB, the measurements shall be repeated after correction of the shift problem.

6.1.2 Locate the microphone at the location selected in 5.3 at approximately 1.5 m above the ground and, if practical, at least 3 m from sound reflecting structures. If circumstances dictate, measurements may be made at other heights and closer to sound reflecting structures providing these facts are noted on a data sheet similar to Figure 1.

6.1.3 Set the sound level meter to the A-weighting network and slow response. Observe the sound level meter during a  $10\text{ s} \pm 2\text{ s}$  sampling period at the start of each consecutive 30 s period. Record the maximum value observed during each sample period,  $L_A$ , on a data sheet such as shown in Figure 2. Take 60 valid readings where a valid reading is one in which the measurements are not affected by intrusive noise sources external to the construction site, such as aircraft, emergency signals, and surface transportation; make a note on the data sheet for each invalid reading.

**CONSTRUCTION SITE SKETCH FORM**

1. Measurer \_\_\_\_\_
2. Date \_\_\_\_\_ Temperature \_\_\_\_\_ Wind Velocity \_\_\_\_\_
3. Construction Site: Location \_\_\_\_\_  
Description \_\_\_\_\_
4. Sound Level Meter: Mfr. \_\_\_\_\_ Model \_\_\_\_\_ S/N \_\_\_\_\_
5. Remarks: \_\_\_\_\_  
\_\_\_\_\_
6. Site sketch showing site boundaries, noise sensitive areas, measurement locations, and major pieces of construction equipment in operation, with distances between the above items, also show wind direction:

SAENORM.COM : Click to view the full PDF of j1075-200006

FIGURE 1—SAMPLE SITE SKETCH DATA SHEET

SAE J1075 Revised JUN2000

Measurer: \_\_\_\_\_ Date: \_\_\_\_\_ Time: \_\_\_\_\_  
 Construction Site: \_\_\_\_\_ Measurement Point: \_\_\_\_\_  
 Remarks: \_\_\_\_\_

**Instructions:**  
 1. Select A-weighting network and "slow" response on meter.  
 2. Calibrate meter using acoustic calibrator and install windscreen.  
 3. Observe for 10 s ± 2 s at the start of each minute and each one-half minute for 30 min, and record maximum level for each observation period.

L <sub>A</sub>	Remarks	L <sub>A</sub>	Remarks
1. _____	_____	31. _____	_____
2. _____	_____	32. _____	_____
3. _____	_____	33. _____	_____
4. _____	_____	34. _____	_____
5. _____	_____	35. _____	_____
6. _____	_____	36. _____	_____
7. _____	_____	37. _____	_____
8. _____	_____	38. _____	_____
9. _____	_____	39. _____	_____
10. _____	_____	40. _____	_____
11. _____	_____	41. _____	_____
12. _____	_____	42. _____	_____
13. _____	_____	43. _____	_____
14. _____	_____	44. _____	_____
15. _____	_____	45. _____	_____
16. _____	_____	46. _____	_____
17. _____	_____	47. _____	_____
18. _____	_____	48. _____	_____
19. _____	_____	49. _____	_____
20. _____	_____	50. _____	_____
21. _____	_____	51. _____	_____
22. _____	_____	52. _____	_____
23. _____	_____	53. _____	_____
24. _____	_____	54. _____	_____
25. _____	_____	55. _____	_____
26. _____	_____	56. _____	_____
27. _____	_____	57. _____	_____
28. _____	_____	58. _____	_____
29. _____	_____	59. _____	_____
30. _____	_____	60. _____	_____

4. Determine  $\bar{L}_A$ : Circle  $L_A$  values within 6 dB of maximum value.  
 $\bar{L}_A = \text{number of circled values} / \text{sum of circled values} = n / \text{sum} = \underline{\quad} / \underline{\quad} = \underline{\quad}$   
 5. Determine  $L_{eq}$ :  
 $n/60 = \underline{\quad}$  Correction (Table 1) =  $\underline{\quad}$   $L_{eq} = \bar{L}_A - \text{Correction} = \underline{\quad}$

FIGURE 2—MANUAL SAMPLING DATA SHEET

6.1.4 On/off-highway vehicles, such as dump trucks, truck/mixers, etc., which occasionally enter, operate on, and leave the site, shall be considered as part of the construction activity while within the site boundaries. However, off-site pass-by of such vehicles in the area of measurement location shall be considered as intrusions, and handled as outlined in 6.1.3.

6.1.5 Determine the representative sound level,  $L_A$ , using:

$$\bar{L}_A = \sum_{i=1}^n (L_A)_i / n \quad (\text{Eq. 1})$$

where:

$L_A$  = The arithmetic average of the  $(L_A)_i$

$n$  = The number of  $(L_A)_i$  values used for computing the arithmetic average

$(L_A)_i$  includes those sound level samples that fall within a range from the maximum sample level to 6 dB below the maximum sample level. For example, if the maximum sample level was 70 dB, all sound level samples between 64 and 70 dB would be valid  $(L_A)_i$ .

6.1.6 Determine a correction to be applied to  $L_A$  to approximate  $L_{eq}$  for the measurement period: divide  $n$  by 60, read the corresponding correction from Table 1, and subtract this value from  $L_A$ .

Then,

$$L_{eq} = L_A - \text{Correction} \quad (\text{Eq. 2})$$

**TABLE 1—CORRECTIONS TO  $L_A$  TO OBTAIN  $L_{EQ}$**

$n/60^{(1)}$ greater than	$n/60^{(1)}$ less than or equal to	Correction, dB <sup>(2)</sup>
0.8	1.0	0
0.7	0.8	1
0.6	0.7	2
0.5	0.6	3
0.4	0.5	4
0.3	0.4	5
0.2	0.3	7
0	0.2	10

1.  $n$  is the number of samples used in the calculation of  $L_A$ .

2. Subtract  $L_A$  to obtain  $L_{eq}$ .

**6.2 Sampling With an Integrating Sound Level Meter**—Equivalent sound level measurements at the construction site boundary adjacent to noise sensitive areas shall be taken with an integrating sound level meter in the following manner:

6.2.1 Calibrate the integrating sound level meter before and after each measurement period, using an acoustic calibrator. Equivalent sound level measurements at the construction site boundary adjacent to noise sensitive areas shall be taken with an integrating sound level meter in the following manner:

6.2.2 Locate the microphone at approximately 1.5 m above the ground and, if practical, at least 3 m from sound reflecting structures. When circumstances dictate, measurements may be made at other heights and closer to sound reflecting structures, providing these facts are noted on a data sheet similar to Figure 1.

## SAE J1075 Revised JUN2000

- 6.2.3 Set the integrating sound level meter to the A-weighting network and slow response (if no slow response switch is present, note that fact in the reporting described in 6.3.1). Estimate what the anticipated maximum and minimum levels will be during the measurement period and set the range of the meter to include these extremes (for example, 40 to 120 dB is a typical range for construction site activity).
- 6.2.4 Start the integrating sound level meter and maintain it in a data collection state for 30 min, exclusive of periods deleted due to intrusions per 6.2.5.
- 6.2.5 If during the measurement period the levels are affected by intrusive noise sources external to the construction site, such as aircraft, emergency signals, and surface transportation, activate the pause or standby switch to inhibit data collection until the intrusion is over.
- 6.2.6 Record the  $L_{eq}$  value at the conclusion of the 30 min measurement period (exclusive of deleted time periods).

### 6.3 Information to be Reported

- 6.3.1 Name of measurer, date, time, construction site, location, type of construction, wind velocity and direction, ambient temperature, sound level meter manufacturer, model, and serial number shall be reported.
- 6.3.2 A site sketch showing construction site boundaries, major pieces of construction equipment operating during the measurement, noise sensitive areas, measurement locations, and distances between these features shall be prepared.
- 6.3.3 The sound level samples, representative sound level, and equivalent sound level at each measurement location shall be reported. Background levels, if measured per 7.1, shall also be reported with the time of measurement and a description of background sound sources and events excluded from the sound level measurement.

### 7. General Comments

- 7.1 It is often desirable to obtain the background sound level at the measurement locations when the construction site is inactive, such as before start-up, during the luncheon break, or after shut-down. The procedures in 6.1 or 6.2 should be used. Include all nonconstruction related noise sources, but exclude intrusive sources, such as emergency signals and aircraft or vehicles passing very close to the microphone, unless such occurrences are representative of typical background sound level conditions at the measurement point.
- 7.2 Only persons technically trained and experienced in the current techniques of sound measurements should select the equipment and conduct the tests.
- 7.3 Proper usage of all test instrumentation is essential to obtain valid measurements. Operating manuals or other literature furnished by the instrument manufacturer should be referred to for both the recommended operation of the instrument and precautions to be observed. Specific items to be considered are:
  - 7.3.1 The type of microphone, its directional response characteristics, and its orientation relative to the ground plane and source of noise.
  - 7.3.2 The effects of ambient weather conditions on the performance of all instruments (for example, temperature, humidity, and barometric/pressure). Instrumentation can be influenced by low temperature and high humidity, and caution should be exercised.
  - 7.3.3 Proper signal levels, terminating impedances, and cable lengths on multi-instrument measurement systems.