

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
B

MA3446™

RATIONALE

FEDERAL SUPPLY CLASS
5306

FIGURE REDRAWN, USAGE NOTE ADDED, SPECS UPDATED.





FIGURE 1

WHEN SHANK LENGTH P ($P = N - 1.5$) IS LESS THAN THD NOM DIA, THE RUNOUT OF SHANK ϕD RELATIVE TO DATUM A SHALL BE MEASURED AT A DISTANCE OF HALF OF THE ACTUAL FULL SHANK LENGTH FROM END OF INCOMPLETE THREAD.

For more information on this standard, visit
<https://www.sae.org/standards/content/MA3446B>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: MA3378



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
CLASSIFICATION: 1210 MPA/730 °C
CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
SHEET 1 OF 9

REV.
B

TABLE 1A - DIMENSIONS D-C

PART NUMBER SEE NOTE 8	NOM DIA REF	THREAD T DESIGNATION	THREAD T MAJOR DIA MOD	D f7 /1/	C
MA3446-050XXX	5	MJ5 x 0.8-4h6h MOD	4.850 - 4.953	4.978 - 4.990	7.0 - 7.2
MA3446-060XXX	6	MJ6 x 1-4h6h MOD	5.820 - 5.953	5.978 - 5.990	8.5 - 8.7
MA3446-070XXX	7	MJ7 x 1-4h6h MOD	6.820 - 6.947	6.972 - 6.987	9.6 - 9.8
MA3446-080XXX	8	MJ8 x 1-4h6h MOD	7.820 - 7.947	7.972 - 7.987	10.8 - 11.0
MA3446-100XXX	10	MJ10 x 1.25-4h6h MOD	9.788 - 9.947	9.972 - 9.987	12.9 - 13.1

TABLE 1B - DIMENSIONS E-AC

NOM DIA REF	E	F	G	H	K	AA	AC
5	11.1 - 11.6	9.0 - 9.3	3.0 - 4.0	2.9 - 3.4	0.3 - 0.5	0.002	0.12
6	12.0 - 12.5	10.5 - 10.8	3.7 - 4.7	3.4 - 3.9	0.5 - 0.7	0.002	0.12
7	13.4 - 13.9	11.6 - 11.9	4.7 - 5.7	4.0 - 4.5	0.5 - 0.7	0.002	0.12
8	14.0 - 14.5	12.8 - 13.1	5.7 - 6.7	4.5 - 5.0	0.5 - 0.7	0.002	0.15
10	16.5 - 17.0	14.9 - 15.2	7.4 - 8.4	5.3 - 5.8	0.6 - 0.8	0.0015	0.15

¹ TOLERANCE GRADE TO ANSI B4.2.



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
 CLASSIFICATION: 1210 MPA/730 °C
 CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
 SHEET 2 OF 9

REV.
 B

TABLE 2 - SHANK LENGTH DIMENSIONS

SIZE	DASH NO. SEE NOTE 8	N MIN	M MAX	L LENGTH	APPROX MASS kg/100
MJ5 x 0.8	050003	3	4.85	14.2 - 14.8	0.454
	050004	4	5.85	15.2 - 15.8	0.470
	050005	5	6.85	16.2 - 16.8	0.486
	050006	6	7.85	17.2 - 17.8	0.502
	050007	7	8.85	18.2 - 18.8	0.518
	050008	8	9.85	19.2 - 19.8	0.534
	050009	9	10.85	20.2 - 20.8	0.550
	050010	10	11.85	21.2 - 21.8	0.567
	050011	11	12.85	22.2 - 22.8	0.583
	050012	12	13.85	23.2 - 23.8	0.599
	050013	13	14.85	24.2 - 24.8	0.615
	050014	14	15.85	25.2 - 25.8	0.631
	050015	15	16.85	26.2 - 26.8	0.647
	050016	16	17.85	27.2 - 27.8	0.663
	050017	17	18.85	28.2 - 28.8	0.679
	050018	18	19.85	29.2 - 29.8	0.695
	050019	19	20.85	30.2 - 30.8	0.711
	050020	20	21.85	31.2 - 31.8	0.728
	050021	21	22.85	32.2 - 32.8	0.744
	050022	22	23.85	33.2 - 33.8	0.760
	050023	23	24.85	34.2 - 34.8	0.776
	050024	24	25.85	35.2 - 35.8	0.792
	050025	25	26.85	36.2 - 36.8	0.808
	050026	26	27.85	37.2 - 37.8	0.824
	050027	27	28.85	38.2 - 38.8	0.840
	050028	28	29.85	39.2 - 39.8	0.856
	050029	29	30.85	40.2 - 40.8	0.872
	050030	30	31.85	41.2 - 41.8	0.887
	050032	32	33.85	43.2 - 43.8	0.921
	050034	34	35.85	45.2 - 45.8	0.953
	050036	36	37.85	47.2 - 47.8	0.985
	050038	38	39.85	49.2 - 49.8	1.017
	050040	40	41.85	51.2 - 51.8	1.050
	050042	42	43.85	53.2 - 53.8	1.082
	050044	44	45.85	55.2 - 55.8	1.114
	050046	46	47.85	57.2 - 57.8	1.146
	050048	48	49.85	59.2 - 59.8	1.178
	050050	50	51.85	61.2 - 61.8	1.211



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
 CLASSIFICATION: 1210 MPA/730 °C
 CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
 SHEET 3 OF 9

REV.
 B

TABLE 2 - SHANK LENGTH DIMENSIONS (CONTINUED)

SIZE	DASH NO. SEE NOTE 8	N MIN	M MAX	L LENGTH	APPROX MASS kg/100
MJ6 x 1	060003	3	5.25	16.2 - 16.8	0.707
	060004	4	6.25	17.2 - 17.8	0.730
	060005	5	7.25	18.2 - 18.8	0.754
	060006	6	8.25	19.2 - 19.8	0.777
	060007	7	9.25	20.2 - 20.8	0.800
	060008	8	10.25	21.2 - 21.8	0.823
	060009	9	11.25	22.2 - 22.8	0.846
	060010	10	12.25	23.2 - 23.8	0.870
	060011	11	13.25	24.2 - 24.8	0.893
	060012	12	14.25	25.2 - 25.8	0.916
	060013	13	15.25	26.2 - 26.8	0.939
	060014	14	16.25	27.2 - 27.8	0.962
	060015	15	17.25	28.2 - 28.8	0.986
	060016	16	18.25	29.2 - 29.8	1.009
	060017	17	19.25	30.2 - 30.8	1.032
	060018	18	20.25	31.2 - 31.8	1.055
	060019	19	21.25	32.2 - 32.8	1.078
	060020	20	22.25	33.2 - 33.8	1.102
	060021	21	23.25	34.2 - 34.8	1.125
	060022	22	24.25	35.2 - 35.8	1.148
	060023	23	25.25	36.2 - 36.8	1.171
	060024	24	26.25	37.2 - 37.8	1.194
	060025	25	27.25	38.2 - 38.8	1.218
	060026	26	28.25	39.2 - 39.8	1.241
	060027	27	29.25	40.2 - 40.8	1.264
	060028	28	30.25	41.2 - 41.8	1.287
	060029	29	31.25	42.2 - 42.8	1.310
	060030	30	32.25	43.2 - 43.8	1.334
	060032	32	34.25	45.2 - 45.8	1.380
	060034	34	36.25	47.2 - 47.8	1.426
	060036	36	38.25	49.2 - 49.8	1.473
	060038	38	40.25	51.2 - 51.8	1.519
	060040	40	42.25	53.2 - 53.8	1.566
	060042	42	44.25	55.2 - 55.8	1.612
	060044	44	46.25	57.2 - 57.8	1.658
	060046	46	48.25	59.2 - 59.8	1.705
	060048	48	50.25	61.2 - 61.8	1.751
	060050	50	52.25	63.2 - 63.8	1.798
	060052	52	54.25	65.2 - 65.8	1.844
	060054	54	56.25	67.2 - 67.8	1.890
	060056	56	58.25	69.2 - 69.8	1.937
	060058	58	60.25	71.2 - 71.8	1.983
	060060	60	62.25	73.2 - 73.8	2.030



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
 CLASSIFICATION: 1210 MPA/730 °C
 CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
 SHEET 4 OF 9

REV.
 B

TABLE 2 - SHANK LENGTH DIMENSIONS (CONTINUED)

SIZE	DASH NO. SEE NOTE 8	N MIN	M MAX	L LENGTH	APPROX MASS kg/100
MJ7 x 1	070004	4	6.25	18.2 - 18.8	1.061
	070005	5	7.25	19.2 - 19.8	1.093
	070006	6	8.25	20.2 - 20.8	1.124
	070007	7	9.25	21.2 - 21.8	1.156
	070008	8	10.25	22.2 - 22.8	1.188
	070009	9	11.25	23.2 - 23.8	1.219
	070010	10	12.25	24.2 - 24.8	1.251
	070011	11	13.25	25.2 - 25.8	1.282
	070012	12	14.25	26.2 - 26.8	1.314
	070013	13	15.25	27.2 - 27.8	1.346
	070014	14	16.25	28.2 - 28.8	1.377
	070015	15	17.25	29.2 - 29.8	1.409
	070016	16	18.25	30.2 - 30.8	1.440
	070017	17	19.25	31.2 - 31.8	1.472
	070018	18	20.25	32.2 - 32.8	1.504
	070019	19	21.25	33.2 - 33.8	1.535
	070020	20	22.25	34.2 - 34.8	1.567
	070021	21	23.25	35.2 - 35.8	1.598
	070022	22	24.25	36.2 - 36.8	1.630
	070023	23	25.25	37.2 - 37.8	1.662
	070024	24	26.25	38.2 - 38.8	1.693
	070025	25	27.25	39.2 - 39.8	1.725
	070026	26	28.25	40.2 - 40.8	1.756
	070027	27	29.25	41.2 - 41.8	1.788
	070028	28	30.25	42.2 - 42.8	1.820
	070029	29	31.25	43.2 - 43.8	1.851
	070030	30	32.25	44.2 - 44.8	1.883
	070032	32	34.25	46.2 - 46.8	1.946
	070034	34	36.25	48.2 - 48.8	2.009
	070036	36	38.25	50.2 - 50.8	2.072
	070038	38	40.25	52.2 - 52.8	2.135
	070040	40	42.25	54.2 - 54.8	2.198
	070042	42	44.25	56.2 - 56.8	2.262
	070044	44	46.25	58.2 - 58.8	2.325
	070046	46	48.25	60.2 - 60.8	2.388
	070048	48	50.25	62.2 - 62.8	2.451
	070050	50	52.25	64.2 - 64.8	2.514
	070052	52	54.25	66.2 - 66.8	2.577
	070054	54	56.25	68.2 - 68.8	2.640
	070056	56	58.25	70.2 - 70.8	2.703
	070058	58	60.25	72.2 - 72.8	2.766
	070060	60	62.25	74.2 - 74.8	2.829
	070062	62	64.25	76.2 - 76.8	2.892
	070064	64	66.25	78.2 - 78.8	2.956
	070066	66	68.25	80.2 - 80.8	3.019
	070068	68	70.25	82.2 - 82.8	3.082
	070070	70	72.25	84.2 - 84.8	3.145



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
 CLASSIFICATION: 1210 MPA/730 °C
 CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
 SHEET 5 OF 9

REV.
 B

TABLE 2 - SHANK LENGTH DIMENSIONS (CONTINUED)

SIZE	DASH NO. SEE NOTE 8	N MIN	M MAX	L LENGTH	APPROX MASS kg/100
MJ8 x 1	080004	4	6.25	19.7 - 20.3	1.442
	080005	5	7.25	20.7 - 21.3	1.484
	080006	6	8.25	21.7 - 22.3	1.525
	080007	7	9.25	22.7 - 23.3	1.566
	080008	8	10.25	23.7 - 24.3	1.608
	080009	9	11.25	24.7 - 25.3	1.649
	080010	10	12.25	25.7 - 26.3	1.690
	080011	11	13.25	26.7 - 27.3	1.732
	080012	12	14.25	27.7 - 28.3	1.773
	080013	13	15.25	28.7 - 29.3	1.814
	080014	14	16.25	29.7 - 30.3	1.855
	080015	15	17.25	30.7 - 31.3	1.897
	080016	16	18.25	31.7 - 32.3	1.938
	080017	17	19.25	32.7 - 33.3	1.979
	080018	18	20.25	33.7 - 34.3	2.021
	080019	19	21.25	34.7 - 35.3	2.062
	080020	20	22.25	35.7 - 36.3	2.103
	080021	21	23.25	36.7 - 37.3	2.144
	080022	22	24.25	37.7 - 38.3	2.186
	080023	23	25.25	38.7 - 39.3	2.227
	080024	24	26.25	39.7 - 40.3	2.268
	080025	25	27.25	40.7 - 41.3	2.310
	080026	26	28.25	41.7 - 42.3	2.351
	080027	27	29.25	42.7 - 43.3	2.392
	080028	28	30.25	43.7 - 44.3	2.434
	080029	29	31.25	44.7 - 45.3	2.475
	080030	30	32.25	45.7 - 46.3	2.516
	080032	32	34.25	47.7 - 48.3	2.599
	080034	34	36.25	49.7 - 50.3	2.681
	080036	36	38.25	51.7 - 52.3	2.764
	080038	38	40.25	53.7 - 54.3	2.846
	080040	40	42.25	55.7 - 56.3	2.929
	080042	42	44.25	57.7 - 58.3	3.011
	080044	44	46.25	59.7 - 60.3	3.094
	080046	46	48.25	61.7 - 62.3	3.176
	080048	48	50.25	63.7 - 64.3	3.259
	080050	50	52.25	65.7 - 66.3	3.341
	080052	52	54.25	67.7 - 68.3	3.424
	080054	54	56.25	69.7 - 70.3	3.506
	080056	56	58.25	71.7 - 72.3	3.589
	080058	58	60.25	73.7 - 74.3	3.671
	080060	60	62.25	75.7 - 76.3	3.754
	080062	62	64.25	77.7 - 78.3	3.836
	080064	64	66.25	79.7 - 80.3	3.919
	080066	66	68.25	81.7 - 82.3	4.001
	080068	68	70.25	83.7 - 84.3	4.084
	080070	70	72.25	85.7 - 86.3	4.166
	080072	72	74.25	87.7 - 88.3	4.249
	080074	74	76.25	89.7 - 90.3	4.331
	080076	76	78.25	91.7 - 92.3	4.414
	080078	78	80.25	93.7 - 94.3	4.496
	080080	80	82.25	95.7 - 96.3	4.579



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
 CLASSIFICATION: 1210 MPA/730 °C
 CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
 SHEET 6 OF 9

REV.
 B

TABLE 2 - SHANK LENGTH DIMENSIONS (CONTINUED)

SIZE	DASH NO. SEE NOTE 8	N MIN	M MAX	L LENGTH	APPROX MASS kg/100
MJ10 x 1.25	100005	5	7.75	24.2 - 24.8	2.542
	100006	6	8.75	25.2 - 25.8	2.607
	100007	7	9.75	26.2 - 26.8	2.671
	100008	8	10.75	27.2 - 27.8	2.736
	100009	9	11.75	28.2 - 28.8	2.800
	100010	10	12.75	29.2 - 29.8	2.865
	100011	11	13.75	30.2 - 30.8	2.929
	100012	12	14.75	31.2 - 31.8	2.994
	100013	13	15.75	32.2 - 32.8	3.058
	100014	14	16.75	33.2 - 33.8	3.123
	100015	15	17.75	34.2 - 34.8	3.187
	100016	16	18.75	35.2 - 35.8	3.252
	100017	17	19.75	36.2 - 36.8	3.316
	100018	18	20.75	37.2 - 37.8	3.381
	100019	19	21.75	38.2 - 38.8	3.445
	100020	20	22.75	39.2 - 39.8	3.510
	100021	21	23.75	40.2 - 40.8	3.574
	100022	22	24.75	41.2 - 41.8	3.639
	100023	23	25.75	42.2 - 42.8	3.703
	100024	24	26.75	43.2 - 43.8	3.768
	100025	25	27.75	44.2 - 44.8	3.832
	100026	26	28.75	45.2 - 45.8	3.897
	100027	27	29.75	46.2 - 46.8	3.961
	100028	28	30.75	47.2 - 47.8	4.026
	100029	29	31.75	48.2 - 48.8	4.090
	100030	30	32.75	49.2 - 49.8	4.155
	100032	32	34.75	51.2 - 51.8	4.284
	100034	34	36.75	53.2 - 53.8	4.413
	100036	36	38.75	55.2 - 55.8	4.542
	100038	38	40.75	57.2 - 57.8	4.671



METRIC AEROSPACE STANDARD

BOLT, MACHINE - TEE HEAD, CHAMFERED
 CLASSIFICATION: 1210 MPA/730 °C
 CLOSE TOL SHANK, UNS N07001, METRIC

MA3446™
 SHEET 7 OF 9

REV.
 B